next generation led

info@nextgenerationled.be
www.nextgenerationled.be
Tel + 32 53 71 09 42

AR111 3-circuit tracklight

Properties

- Ideal in combination with AR111 spots from Soraa or RGBW (see product sheets below)
  Productsheet AR111 RGBW 6~17W
  Productsheet AR111 12W
  Productsheet AR111 18W
- Tin-plate housing
- Driver included
- IP20
- 3-phase adapter included
- 1100 grams
- Power factor > 0.9
- 350° rotatable and 90° tiltable
- Dimmable only with 350ma version
- 3y warranty on driver

Application

Indoor, retail store, bar, restaurant, living room, bedroom, kitchen, etc...

Specifications

SORAA AR111



ngl
next generation led

AR111 3-circuit tracklight

REFERENCE	LUMEN	COLOR	BEAM	DIMMABLE	MANUFACTURER
500-0123	AR111 3-CIRCUIT TRACKLIGHT BLACK 3y warranty on driver				
100-0502	10 W 400-950lm	RGBW	15 °	Yes	NGL
100-0503	10 W 400-950lm	RGBW	24 °	Yes	NGL
100-0504	10 W 400-950lm	RGBW	38 °	Yes	NGL
100-0505	10 W 400-950lm	RGBW	60 °	Yes	NGL
100-0013	18,5 W CRI 95 930 lm	2700 K	9 °	Yes	SORAA
100-0014	18,5 W CRI 95 930 lm	2700 K	25 °	Yes	SORAA
100-0015	18,5 W CRI 95 930 lm	2700 K	36 °	Yes	SORAA
100-0016	18,5 W CRI 95 930 lm	2700 K	60 °	Yes	SORAA
100-0017	18,5 W CRI 95 1000 lm	3000 K	9 °	Yes	SORAA
100-0018	18,5 W CRI 95 1000 lm	3000 K	25 °	Yes	SORAA
100-0019	18,5 W CRI 95 1000 lm	3000 K	36 °	Yes	SORAA
100-0020	18,5 W CRI 95 1000 lm	3000 K	60 °	Yes	SORAA
100-0021	18,5 W CRI 95 1040 lm	4000 K	9 °	Yes	SORAA
100-0022	18,5 W CRI 95 1040 lm	4000 K	25 °	Yes	SORAA
100-0023	18,5 W CRI 95 1040 lm	4000 K	36 °	Yes	SORAA
100-0024	18,5 W CRI 95 1040 lm	4000 K	60 °	Yes	SORAA
100-0025	18,5 W CRI 95 1050 lm	5000 K	9 °	Yes	SORAA
100-0026	18,5 W CRI 95 1050 lm	5000 K	25 °	Yes	SORAA
100-0027	18,5 W CRI 95 1050 lm	5000 K	36 °	Yes	SORAA
100-0028	18,5 W CRI 95 1050 lm	5000 K	60 °	Yes	SORAA
100-0101	12,5 W CRI 95 575 lm	2700 K	8 °	Yes	SORAA
100-0102	12,5 W CRI 95 575 lm	2700 K	25 °	Yes	SORAA
100-0103	12,5 W CRI 95 575 lm	2700 K	36 °	Yes	SORAA
100-0104	12,5 W CRI 95 575 lm	2700 K	50 °	Yes	SORAA
100-0105	12,5 W CRI 95 620 lm	3000 K	8 °	Yes	SORAA
100-0106	12,5 W CRI 95 620 lm	3000 K	25 °	Yes	SORAA
100-0107	12,5 W CRI 95 620 lm	3000 K	36 °	Yes	SORAA
100-0108	12,5 W CRI 95 645 lm	3000 K	50 °	Yes	SORAA
100-0109	12,5 W CRI 95 645 lm	4000 K	8 °	Yes	SORAA
100-0110	12,5 W CRI 95 645 lm	4000 K	25 °	Yes	SORAA
100-0111	12,5 W CRI 95 645 lm	4000 K	36 °	Yes	SORAA
100-0112	12,5 W CRI 95 645 lm	4000 K	50 °	Yes	SORAA