



next generation led

info@nextgenerationled.be  
www.nextgenerationled.be  
Tel + 32 53 71 09 42

# Inground Light

## Properties

- Lifespan L70 %: > 50.000hr
- Immediate start regardless of temperature or humidity
- No mercury or toxic gasses
- Unique and innovative induction power supply
- 316L stainless steel front cover
- Aluminum alloy body
- 2000KG drive over
- SMD2835 LED chip
- Glass top, 10mm thick
- Induction to LED transfer greatly improving waterproof rating
- Head can be replaced whilst connected
- Warranty: 5 y



IP 67      Extra safe      Induction power supply

## Specifications

Linear inground light	9W	12W
Input voltage	AC110 - 220V	
Lumen output	675-720lm	1350-1450lm
Color rendering index	RA ≥ 80	
Color temperature	3000K, 4000K, 6000K	
Temperature in use	- 20°C ~ 45°C	
Beam angle	120°	
Dimension (DxH)	600x47,5x92mm	1000x47,5x92mm

## Application

Pathways, feature highlighting, facade lighting, driveways, garden lighting, decking

Updated: November 2017



## Inground Light

REFERENCE	WATT	LUMEN	COLOR	BEAM ANGLE	DIMMABLE
290-0150	9W	675-720lm	3000K	120°	NO
290-0151	9W	675-720lm	4000K	120°	NO
290-0152	9W	675-720lm	6000K	120°	NO
290-0153	12W	1350-1450lm	3000K	120°	NO
290-0154	12W	1350-1450lm	4000K	120°	NO
290-0155	12W	1350-1450lm	6000K	120°	NO

