next generation led

info@nextgenerationled.be www.nextgenerationled.be Tel + 32 53 71 09 42

TL EXTERNAL DRIVER



- Lifespan L70 %: > 50.000 hours
- SMD2835 (Surface Mounted Device)
- Energy savings up to 70%
- Aluminum cooling surface
- External driver
- Flicker free to reduce the eyestrain
- Will not break when dropped
- Environment friendly : no mercury or toxic gasses
- 80% more efficiency compared to traditional fluorescent
- Immediate start regardless of temperature or humidity
- Retro-fit = easy installation
- Warranty: 5 years





Retro-fit

Extern Drive

vy Duty

Specifications

TL F SERIE	60 CM	90 CM	120 CM		150 (CM
Power	10 W	15 W	20 W	24 W	24 W	30 W
Number of LED's	78	120	156	156	156	156
Input voltage	AC 85~165/ 165 ~265 V					
Diameter	30 mm					
Color temperature	3000 K (ww) / 4000 K (nw) /5000 K (pw)					
Powerfactor	>0.8					
Cover	Available in striped or frosted cover					
Color rendering index	Standard CRI>80, Optional CRI>90					

Application

In production facilities where tubes are exposed to higher environmental temperatures.





CIE 1931

The CIE color space, developed in 1931, is still used to define colors, and as a reference for other color spaces. The figure is a two-dimensional display of colors of the same intensity (brightness), which is based on observations of color measurements by people.





SPECTRUM

Isaac Newton used the Latin word spectrum to define the color series which arose when he dropped a bundle of sunlight through a glass prism. The color spectrum consists of the colors of the rainbow with the color sequence red-orange-yellow-green-blue-indigo-violet, which corresponds to bearish wave length (increasing frequency) of the light waves.

C78 377

ANSI C 78.377 is now the standard for color quality, as determined by the American National Standards Institute. ANSI recommends lamp manufacturers to stay within a 4-step ellipse. This means that manufacturers with a particular focus on the CIE diagram have a broad range of observable differences.



										e = 8
R1										$a = \frac{86}{85}$
R 2					_					92
			-		-		-	-	-	07
no 04										97
R4										85
R5 📃			_	_						85
R6										91
R7	•									87
R8							1.00			68
							- 11			00
R9										21
R10										82
R11							_	_		85
R12										74
R13										87
R14			,							qq
D16	-	-	_	-	-	_	-	-		70
RID	10	20	30	40	50	60	70	80	۹n	100
0	10	20	00	-10	30	00	10	00	30	100

CRI HISTOGRAM

The color reproduction of a light source indicates whether the color of an object can be displayed true to nature. The graph shows whether we can accurately determine color, depending on the color rendering properties of the light source.

Ra = average of R1 to R8

Re = average of R1 to R15

R9 = saturated red. Should be as high as possible.

SDCM

SDCM is an acronym which stands for Standard Deviation Colour Matching. SDCM has the same meaning as a "MacAdam ellipse". A 1-step MacAdam ellipse defines a zone in the CIE 1931 2 deg (xy) colour space within which the human eye cannot discern colour difference. Most LEDs are binned at the 4-7 step level, in other words you certainly can see colour differences in LEDs that are ostensibly the same colour.

<u>SDCM</u>	<u>CCT @ 3000K</u>	ΔUV
1x	±30K	±0.0007
2x	±60K	±0.0010
4x	±100K	±0.0020
7-8x	±175K	±0.0060

0.433 x = 0.4364, y = 0.4040. CCT = 3008K 1 SDCM 0.423 3 SDCM 5 SDCM 0.413 7 SDCM
0.423 3 SDCM 5 SDCM 0.413 7 SDCM
0.413 7 SDCM
0.403
0.393
3000K
0.383
0.373



ENERGYLABEL

Electrical appliances carry an energy label. This label prints the so-called energy efficiency score in classes. These classes range from 'very energy efficient' (A++) to 'very waste of energy' (E). A more expensive new device may eventually turn out to be cheaper if the energy score is good. IPEA is the new system for luminaire energy efficiency assessment.





BEAM

The Illuminance Cone Diagram indicates the maximum illuminance at different distances from the fixture.



The polar luminous intensity graph illustrates the distribution of luminous intensity, in candelas, for the transverse (solid line) and axial (dashed line) planes of the luminaire. The shown curve provides a visual guide to the type of distribution expected from the luminaire e.g. wide, narrow, direct, indirect... in addition to intensity.





TL EXTERNAL DRIVER

REFERENCE	LENGTH	WATT	COVER	COLOR	DIMMABLE
275-0100	60 CM	10 W	STRIPED	3000 K	No
275-0101	60 CM	10 W	STRIPED	4000 K	No
275-0102	60 CM	10 W	STRIPED	5000 K	No
275-0103	90 CM	15 W	STRIPED	3000 K	No
275-0104	90 CM	15 W	STRIPED	4000 K	No
275-0105	90 CM	15 W	STRIPED	5000 K	No
275-0106	120 CM	20 W	STRIPED	3000 K	No
275-0107	120 CM	20 W	STRIPED	4000 K	No
275-0108	120 CM	20 W	STRIPED	5000 K	No
275-0109	120 CM	24 W	STRIPED	3000 K	No
275-0110	120 CM	24 W	STRIPED	4000 K	No
275-0111	120 CM	24 W	STRIPED	5000 K	No
275-0112	150 CM	24 W	STRIPED	3000 K	No
275-0113	150 CM	24 W	STRIPED	4000 K	No
275-0114	150 CM	24 W	STRIPED	5000 K	No
275-0115	150 CM	30 W	STRIPED	3000 K	No
275-0116	150 CM	30 W	STRIPED	4000 K	No
275-0117	150 CM	30 W	STRIPED	5000 K	No

